Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

Polyurethane resin P2600, P2654, P2662

Chemical name : P-MDI CAS-number : 9016-87-9 Reach reg.nrs. : 01-2119457024-46

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use:

Insulating and sealing

Unsuitable use: Spraying

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Filoform B.V Postbus 2

NL-4190 CA Geldermalsen

1.4 Emergency telephone number

The UK National Poisons Emergency number is 0870 600 6266

2. Hazards identification

2.1 Classification of the substance or mixture

Classification according to directive (EG) nr. 1272/2008 [CLP]

Acute tox. 4 Eye Irrit. 2 Skin Irri. 2 STOT SE 3 Skin Sens. 1 Resp Sens. 1 Carc. 2 STOT RE 2

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer if inhaled. (see chapter 11)

H373 May cause damage to organs through prolonged or repeated exposure.

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



2.2 Label elements

Labelling according to directive (EG) nr. 1272/2008

Hazard pictograms:





GHS07 GHS08

Signal word: Danger.

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

H351 Suspected of causing cancer if inhaled. (see chapter 11)

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.
P233+403 Store in a well-ventilated place. Keep container tightly closed.

P302+352 IF ON SKIN: Wash with soap and water.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and

easy to do - continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Hazardous components for labelling: DIPHENYLMETHANEDIISOCYANATE, ISOMERES UND HOMOLOGUES

Classification according to directive 67/548/EEG or directive 1999/45/EG

Hazard pictogram

Xn Harmful

R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin.
R40 Limited evidence of a carcinogenic effect

R42/43 May cause sensitization by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

S23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

S36/37 Wear suitable protective clothing and gloves.

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where

possible).

2.3 Other hazards

Mixing of the components gives expansion and generates heat.

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



3. Composition/information on ingredients

3.1 Substances

3.2 Mixtures

Contains: P-MDI CAS-number: 9016-87-9 10 – 30 % Xn R48/20

Mixture of polyols. 70 - 90 %

4. First aid measures

4.1 Description of first aid measures

After inhalation:

Supply fresh air and call for a doctor.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. If symptoms persist consult a doctor.

After eye contact:

Rinse opened eye for 15 minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth immediately and then drink plenty of water, avoid vomiting, consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Dangers:

Symptoms may be delayed.

Symptoms:

Tightness in the chest, coughing and breathing difficulties.

4.3 Indication of any immediate medical attention and special treatment needed

To treat the symptoms no specific antidote is known. The contamination, monitoring of vital functions.

To prevent pulmonary edema: corticosteroid-containing metered dose inhaler.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Powder or water spray and CO₂.

Unsuitable extinguishing media:

Water with full jet.

5.2 Special hazards arising from the substance or mixture

In case of fire or overheating:

Hydrogen cyanide (HCN), carbon monoxide (CO), carbon dioxide (CO₂), nitrogen oxides (NOx), isocyanate.

5.3 Advice for firefighters:

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Do not inhale gases from explosion, fire or overheating.

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



Additional information

Cool threatening packaging with water spray. Fire residues and contaminated extinguishing water in accordance with local regulations when handling waste. Contaminated extinguishing water separately, do not allow into drains, surface water or effluent.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General:

Ventilate and wear personal protective clothing.

When gases/vapours arise:

Wear respiratory protection.

6.2 Environmental precautions

Do not allow unmixed material to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up

Clean-up procedures:

Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

Disposal:

Treating liquids as chemical waste. Treating solids as household waste.

6.4 Reference to other sections food stuff

Information regarding exposure route (H351) in Section 2.2, is located in section 11.

Information regarding exposure controls, personal protection and disposal considerations can be found in section 8 and 13.

7. Handling and storage

7.1 Precautions for safe handling

Take care of a good ventilation of storage and workplace.

Processing temperature 0°C to + 35°C. Product not used for other purposes than intended.

7.2 Conditions for safe storage, including any incompatibilities

Store in closed packaging, in a dry and well-ventilated place.

Short term, between: -10°C until + 50°C

Storage for a long term, between: +15 until +25°C

7.3 Specific end use(s)

Sealing and insulating.

8. Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

Not required

Continuous repetitive movements and work in unventilated areas:

101-68-8: 4,4'-METHYLENEDIPHENYL DIISOCYANATE

TGG value (8hours) 20 ug/m³ (Workplace Exposure Limit UK)

TGG value (15 minutes) 50 ug/m³ (DFG 2008 Germany)

PNEC

Is not applicable.

DNEL

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



Is not applicable.

8.2 Exposure controls

General protection and hygiene measures:

- Avoid breathing vapour and mist.
- Avoid contact with skin, eyes and clothing.
- Do not eat, drink or smoke at work.
- Remove contaminated clothing immediately.
- Before breaks and at the end of the working day wash hands thoroughly.
- Keep away from food and drinks.

8.2.1 Appropriate engineering controls

Only use in a well ventilated area.

8.2.2 Individual protection measures, such as personal protective equipment

Respiratory protection:

No personal respiratory protective equipment required within the scope. With inadequate ventilation use suitable respiratory protection

Hand protection:

Impermeable gloves of rubber or plastics.

Eye/face protection:

Safety glasses with side-shields.

Skin protection:

Safety shoes, closed working clothes.

8.2.3 Environmental exposure controls

The two components package requires careful handling.

Fluids should be carefully collected and be treated as hazardous waste.

Mixed product forms an inert substance and has no environmental objections.

Additional Information:

Occupational exposure:

The major risk with repeated (skin) contact is getting an allergy (hypersensitivity) to one or

several components. Once developed allergies, allergic reactions may occur with each subsequent (skin) contact with isocyanates.

To strictly follow the "Exposure controls/personal protection" the occurrence of hypersensitivity may be limited.

9. Physical and chemical properties

9.1.1 General properties

Colour:

Black/brown

Form:

liquid

Odour:

Smells like earth, musty.

9.1.2 Information on basic physical and chemical properties

Melting point/freezing point:

< 10 °C

Initial boiling point and boiling range:

330 °C (1.013 mbar)

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



Flash point:

> 204 °C

Evaporation rate:

Value can be estimated on the basis of the Henry's Law constant of or on the vapour pressure.

Flammability (solid, gas):

Non-flammable.

Upper/lower flammability or explosive limits:

For these fluids are not relevant for classification and labelling.

Ignition temperature:

> 600 °C

Vapour pressure at 25°C:

< 0.01 Pa

Relative density:

ca. 1,22 (20°C)

Partition coefficient: n-octanol/water:

N/A

Relative vapour density at 20°C:

8.5

Solubility in water:

Hardener component reacts slowly with water at the interface to insoluble polyurea with high melting point. In this reaction, CO2 is released. Cured product is inert and insoluble in water.

Viscosity at 25°C:

>200 mPa.s

Explosive properties:

Not explosive.

Oxidising properties:

Not oxidising.

9.2 Other information

Miscibility with water:

Reacts with water.

Other information:

If necessary, the information on other physical and chemical parameters listed in this section.

10. Stability and reactivity

10.1 Reactivity

No hazardous reactions if the regulations / notes for storage and handling are followed. Upon mixing of the components expansion occurs, the volume will increase factor of 10.

10.2 Chemical stability

The product is stable, if the regulations / notes for storage and handling are followed.

10.3 Possibility of hazardous reactions

Reactions with water with formation of carbon dioxide. Do not mix with other chemicals.

10.4 Conditions to avoid

Conditions to avoid:

None, if the regulations / notes for storage and handling are followed.

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



10.5 Incompatible materials

Materials to avoid:

Acids, alcohols, amines, water and alkalis.

10.6 Hazardous decomposition products

No hazardous decomposition products, if the regulations / notes for storage and handling are followed.

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

After a single ingestion and contact with skin and practically non-toxic. Moderate toxicity after short-term inhalation

LD50 rat (oral) : > 10.000 mg/kg LC50 rat (inhalatoir) : ca 0,500 mg/l 4h LD50 rabbit (dermal) : > 10.000 mg/kg

Skin corrosion/irritation:
Irritating to eyes and skin

Sensibility of the respiratory system and skin:

The substance has a sensitizing effect on the respiratory system and skin.

Germ cell mutagenicity:

The substance exhibited in various test systems microorganisms and cell cultures a modifying effect on the genetic material, however, in experiments on mammals could not be confirmed.

Carcinogenicity:

Indications of possible carcinogenic effect in animal experiments. However, the relevance of the results to humans is not confirmed. The substance is long-term tested as respirable aerosol.

Reproductive toxicity:

Repeated inhalation uptake of the substance did not cause damage to the reproductive organs.

STOT-single exposure:

May be irritating to the respiratory system.

STOT-repeated exposure:

The substance may cause on the basis of experimental studies on animals by repeated inhalation of small amounts of damage to the lungs.

Aspiration hazard:

No aspiration hazard expected.

12. Ecological information

12.1 Toxicity

With high probability unharmful to aquatic organisms. No toxic effects in the aquatic environments.

12.2 Persistence and degradability

Non-biodegradable.

12.3 Bio accumulative potential

Concentrates negligible in organisms.

12.4 Mobility in soil

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



Adsorption to solid soil is not expected.

12.5 Results of PBT and vPvB assessment

N/A

12.6 Other adverse effects

The product does not contain substances from Annex I to Regulation (EC) 2037/2000 on ozone depleting substances.

Additional information:

The product does not contains halogens.

Other Eco toxicological advice:

Unmixed product: Do not release untreated into natural waters.

13. Disposal considerations

13.1 Waste treatment methods

Cured product residue and the resin packing can be treated as household waste.

Plastics and the carton can be recycled.

Treating liquids as chemical waste in accordance with local authority requirements.

14. Transport information

Not classified as a dangerous goods under transport regulations: ADR, RID, ADNR, IMDG/GGVSee, ICAO/IATA

14.1 UN number

N/A

14.2 UN proper shipping name

N/A

14.3 Transport hazard class(es)

N/A

14.4 Packing group

N/A

14.5 Environmental hazards

N/A

14.6 Special precautions for use

N/A

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

NI/A

Special precautions for transport

Hazard map:

No hazard map required.

Hazard symbol:

None

Different goods with different identification numbers are packaged within the limited quantities in a single package.

The substances and their packaging meets section 3.4 of the ADR / RID / ADNR

Date: 20-01-2014 version 19-06-2015

Product: Polyurethane Resin



15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

If other legal rules that are not mentioned elsewhere in this safety data sheet, then it is described in this subsection.

15.2 Chemical safety assessment

N/A

16. Other information

Full text of H and P phrases referred to under sections 2 and 3.

H315 H317 H319 H332 H334 H335 H351 H373	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer if inhaled. (see chapter 11) May cause damage to organs through prolonged or repeated exposure.
P271 P280 P285 P233+403 P302+352 P305+351+338	Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection. Store in a well-ventilated place. Keep container tightly closed. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

Legal Disclaimer:

This product is intended for filling, sealing and fixing. Always use the manufacturer's instructions. Local laws and regulations should be the recipient of the product on its own responsibility are met. The above information is believed to be correct but does not purport to be complete. Filoform is not responsible for any damage resulting from handling or contact with the above product.

This safety data is made on 24-03-2015 and prepared in accordance with Regulation (EC) No. 453/2010 Status: Final