



GW 12-70

Counter trough, dia. 12-70 mm

The counter troughs GW 12-70 protect the cables and improve cable support on the profile. They are suitable for cables with a maximum diameter of 70 mm and are made of polyethylene.

polyethylen

| Products | L | D | Ø _c | W |
|----------|-------|------------|----------------|----------|
| GW 12 | 40 mm | 9 - 12 mm | 12 mm | 0,001 kg |
| GW 16 | 40 mm | 13 - 16 mm | 16 mm | 0,001 kg |
| GW 20 | 40 mm | 17 - 20 mm | 20 mm | 0,002 kg |
| GW 24 | 40 mm | 21 - 24 mm | 24 mm | 0,002 kg |
| GW 28 | 40 mm | 25 - 28 mm | 28 mm | 0,003 kg |
| GW 32 | 40 mm | 29 - 32 mm | 32 mm | 0,003 kg |
| GW 36 | 40 mm | 33 - 36 mm | 36 mm | 0,004 kg |
| GW 40 | 40 mm | 37 - 40 mm | 40 mm | 0,005 kg |
| GW 48 | 40 mm | 41 - 48 mm | 48 mm | 0,007 kg |
| GW 56 | 40 mm | 49 - 56 mm | 56 mm | 0,010 kg |
| GW 64 | 40 mm | 57 - 64 mm | 64 mm | 0,011 kg |
| GW 70 | 40 mm | 65 - 70 mm | 70 mm | 0,012 kg |

L: length

D: diameter

Ø_c: Suitable for max. cable diameter

W: Weight per storage unit

DETAIL AND APPLICATION IMAGES

PRODUCT INFORMATION

